VANDERSANDEN

Product name		Production location
Medoc (Without Chamfered Edge, with spacers)	A4-12	Spijk

Format	
Moulding method	Mould
WF85: 206 x 51 x 88 mm	Between batches the average size and color may slightly differ.

Essential Characteristics - EN1344		
CE		
Reaction to fire	Klasse A1	
External fire performance	NPD	
Dangerous substances	NL-BSB	
Transverse breaking load	T4	Category
Unpolished slip/skid resistance USRV	U3	Category
Thermal conductivity	NPD	
Durability against freeze thaw	FP100	Category
Sustainable slip/skid resistance	U2	Category

Other Characteristics - EN1344 & BRL 2360		
Paver quality 1	A4-12	Category
Paver quality 1 Tolerances	<= 0,4 $\sqrt{\text{dimensions}}$	
Paver quality 1 Range	R1	Category
Water absorption	<= 5% m/md	
Abrasion resistance	A2	Category
Acid resistance	C	Category

Other Characteristics - PTV 910		
Standardized Quality Classes	B	
Water absorption	W2 (<=5%,<=6%)	

Storage & handling	Cutting
- Stock pavers on a clean surface and cover them - Blend from different pavers (pack) at the same time - Do not clean fresh masonry with hydrochloric acid	Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).

No rights can be derived from this document