

Product name		Product group	Production location
Old Victorian		X2	Spouwen
Colour			
a shade of light red, red brown and white to brown black with appearance of reclaimed brick			
Format			
Moulding method		Hand form	
WF: 212 x 100 x 50 mm		Between batches the average size and color may slightly differ.	
Essential Characteristics - EN771-1			
 NPD			
Dimensional tolerances	Tm (15 x 12 x 10 mm)		
Range	Rm (30 x 20 x 15 mm)		
Active Soluble Salts	S1		
Mean Compressive strength	NPD		Tested to the bed face
Normalized Compressive strength	≥ 10 N/mm ²		Tested to the bed face
Dimensional stability	NPD		
Bond Strength general	NPD		
Bond Strength thin layer	NPD		
Reaction to fire	A1		Category
Water absorption	≤ 25% m/md		
Water vapour permeability	NPD		
Net dry density	NPD		
Gross dry density	NPD		
Thermal conductivity Lambda 50/50	≤ NPD		
Durability against freeze thaw	F2		
Dangerous substances	NL-BSB		According to Annex ZA 3
Other Characteristics			
Initial rate of water absorption - Non-coated Bricks	NPD		Value according EN771-1:2011 - 5.3.8
Initial rate of water absorption - Coated bricks	NPD		Value according EN771-1:2011 - 5.3.8
Freeze/thaw resistance	NPD		B 27-009
Thermal conductivity Lambda 90/90	NPD		
Thermal conductivity Lambda Ui	NPD		
Thermal conductivity Lambda Ue	NPD		
			
Storage & handling		Cutting	
<ul style="list-style-type: none"> - Store packs on a clean surface and cover them - Process from multiple packs at the same time - Follow the Vandersanden processing guidelines 		Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).	
*All our Coated bricks are only coated on the facing sides. Coated products are specially labeled and recognisable with a "C" logo on the top left-hand side of the packaging. Always check if using coated or non-coated bricks. Match the mortar to the specified initial water absorption.			